



### CLASSIC

The Classic decorative film allows you to effectively personalise your windows and glass partitions. It provides privacy thanks to its frosted aspect angel hair effect patterning.



SOLAR SCREEN® Warranty  
**5 YEARS**



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **152 cm**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	NC %
Reflection of external visible light	NC %
Reflection of internal visible light	NC %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio :	
Solar energy reflection	NC %
Solar energy absorption	NC %
Solar energy transmission	NC %
Reduction in Solar Glare	NC %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type : Interior	
Roll length	50 m
Film composition	PET
Thickness	40 μ

Colour from the outside : WHITE

### CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes    ! Caution    ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.